



TRAC CHAIN[®]

Ideal for theatrical rigging applications where adjustability is required

Grade 80 alloy material in accordance with ASTM A391 with 1/2" diameter & 6 ton working load limit

Heat treated with each link proof tested to ensure weld & material integrity

PTC8 hallmark & traceability code every 5 links & USA on the back of each link

Manufactured and tested in accordance with ASTM A391* 4:1 Design Factor

Black TRAC[®] finish

Made in the USA

* Standard Specifications for Grade 80 Alloy Steel Chain

STOCK# Bulk	Chain Size (inches)	Wire Dia. (inches)	Inside Link Dim. (Inches)		Quantity Per Pkg (Ft.)	Net Wt. Lbs.	WLL	
			Length	Width			Lbs.	Kgs.
5058051	1/2	0.53	3.74	0.92	100	200	12,000	5,443
5058052	1/2	0.53	3.74	0.92	250	500	12,000	5,443
5058053	1/2	0.53	3.74	0.92	500	1000	12,000	5,443

STOCK# Tagged Assembly	Chain Size (inches)	Length (feet)	Net Wt. Lbs.	Qty Per Drum
5058003	1/2	3	6.3	20
5058004	1/2	4	8.1	15
5058005	1/2	5	10.6	15
5058006	1/2	6	12.5	10
5058007	1/2	7	14.3	10
5058008	1/2	8	16.2	8
5058009	1/2	9	18.1	7

Custom Lengths Also Available!

Kito Crosby

1416 East Sanborn Street • Winona, MN • 55987-5349
 kitocrosby.com/peerless • PHONE: (800) 873-1916 • FAX: (800) 356-1149
 27.69 © Kito Crosby 2024. All rights reserved

